24MY ISUZU D-MAX SPECIFICATIONS

Engine	3.0L	1.9L
Series	Isuzu 4JJ3-TCX	RZ4E-TC
Description	3-litre turbo-diesel, in-line 4-cylinder, DOHC, 16-valve with Diesel Particulate Diffuser (DPD)	1.9-litre turbo-diesel, in-line 4-cylinder, DOHC, 16-valve with Diesel Particulate Diffuser (DPD)
Maximum torque	450Nm @ 1600→2600 rpm (automatic & manual)	350Nm @ 1800 \rightarrow 2600 rpm (automatic and manual)
Maximum power	140kW @ 3600 rpm	110kW @ 3600 rpm
Bore x stroke	95.4mm x 104.9mm	80mm x 94.4mm
Displacement	2999cc	1898cc
Compression ratio	16.3 : 1	15.9: 1
Cylinder head	Isuzu-patent special aluminium alloy	Isuzu-patent special aluminium alloy
Valve gear	Chain-driven dual overhead camshafts, roller rockers, 4 valves/cylinder	Chain-driven dual overhead camshafts, roller rockers, 4 valves/cylinder
Induction	Electronic high pressure common rail direct fuel injection with VSS (Variable Swirl System) and intercooled electric control VGS (Variable Geometry System) turbocharger	Electronic high pressure common rail direct fuel injection with VSS (Variable Swirl System) and intercooled electric control VGS (Variable Geometry System) turbocharger
Cylinder block	Cast iron upper with induction-hardened cylinder bores, cast alloy lower	Cast iron upper with induction-hardened cylinder bores, cast alloy lower
Emission level	Euro 5	Euro 5
Alternator	90 amp with Intelligent Battery Sensor (IBS)	90 amp with Intelligent Battery Sensor (IBS)

Transmissions

11411311113314113						
Manual	275mm diameter 1.9L Engine: Isuzu	clutch plate and MVL-6Y 6-spee	dual mass flywhe	el n torque capacity a	and output reduction	
Automatic	with fuel-saving lo	ck-up torque co ransmission Cor	nverter on gears 3, ntrol: holds gear in v	4, 5 and 6	ectronically control cents, selects gear	
Ratios: 1	3.0L Turbo 1st 2nd 3rd 4th 5th 6th Reverse	6-speed Manual 4.942 2.452 1.428 1.000 0.749 0.634 4.597	6-speed Automatic 3.600 2.090 1.488 1.000 0.687 0.580 3.732	1.9L Turbo 1st 2nd 3rd 4th 5th 6th Reverse	6-speed Manual 4.942 2.686 1.527 1.000 0.749 0.634 4.597	6-speed Automatic 3.600 2.090 1.488 1.000 0.687 0.580 3.732
Final drive	4x2 4x4	3.727 3.727	3.727 3.727	4x2	4.100	4.100 4.100
Transfer gearing	Snorkelled diff bre 4x4 low-range 4x4 high-range	athers to increas 2.482 1.000	se fording depth ar 2.482 1.000	id reduce mud blo	ckage	2.482 1.000
4x4 system	"Terrain Comman rear differential loc		'shift on the fly' 2-h	nigh <→ 4-high sele	ection at up to 100	km/h, 4-low with
Drivetrain system	TCS (Traction Con	trol System) on	all model variants			

Steering

Electric power steering with speed-sensing steering feel (light at low speed, heavy at high speed); tilt and telescopic adjustable steering wheel Engine-speed-sensitive variable capacity Electric power system; 3.84 turns lock-to-lock via tiltadjustable steering wheel

Chassis

Separate, full-length heavy-duty chassis with 8 cross members on all models

Front suspension Independent, high-ride, coil springs, gas shock

absorbers, upper and lower wishbones, stabiliser bar

Rear suspension

All Cab Chassis models: Heavy Duty alloy-steel overslung long-span semi-elliptic leaf springs; gas shock absorbers

4x2 and 4x4 models: Alloy-steel overslung long-span semi-elliptic leaf springs; gas shock absorbers

Axles

Front

Independent 4x4: fully floating with outer CV, inner double offset joints and equal length driveshafts. Rating: 1450kg

Rear

Rigid semi-floating banjo with hypoid final drive and dual tapered needle roller bearings, Rating: 1910kg

Brakes

Anti-lock Brake System (ABS) with Electronic Brakeforce Distribution (EBD), Electronic Stability Control (ESC), Emergency Brake Assist (EBA), Traction Control System (TCS), Rollover Mitigation, Hill Start Assist (HSA), Hill Descent Control (HDC) and Trailer Sway Control (TSC)

320mm dia, ventilated front discs with 2-piston calipers, 295mm rear drums

Power-assisted via 10" servo unit; central pull up park brake

Wheels and Tyres

SX	17" x 7" drilled Silver-Finish Steel; 255 / 65 R17 All-Terrain
LS-M	17" x 7" alloy; 255 / 65 R17 All-Terrain
X-RIDER	17" x 7" alloy; 255 / 65 R17 All-Terrain
LS-U and LS-U+	18" x 7.5" alloy; 265 / 60 R18 Highway-Terrain
X-TERRAIN	18" x 7.5" matte Dark Grey Alloy; 265 / 60 R18 Highway-Terrain
All Models	Full size steel spare wheel

Service Plus

Μ

R A

FI S

Varranty	For the ultimate peace of mind, every Isuzu D-MAX comes standard with a comprehensive, bumper-to-bumper 6 years/150,000km warranty^.
oadside ssistance	Enjoy up to 7 years Roadside Assistance ^{<} when you complete your scheduled services at a Participating Isuzu UTE Dealer.
lat Price ervicing	As an owner you will get access to our Flat Price Servicing ^{>} Program. The FPS Program covers the first 5 Scheduled Services at \$449 per service in line with the Scheduled Service Intervals.

>The Flat Price Servicing Program ("FPS Program") applies to FPS Eligible Vehicles (excludes Rental & Government Customers) at Participating Isuzu UTE Dealers only. For 24MY and later vehicle models, the Flat Price Servicing covers the first 5 Scheduled Services up to 5 years/75.000km (whichever occurs first). FPS Program is subject to change. For full terms & conditions, current pricing & model eligibility visit isuzuute.com.au/flat-price-service-disclaimer. ^6 vears/150.000km (whichever occurs first), for Isuzu UTE Vehicles with a Warranty Start Date on or after 1/1/19. Excludes travs & accessories. "The Roadside Assistance Program ("RSA Program") provides Coverage to RSA Eligible Vehicles (Private, ABN and Business Fleet Customers only) with a Warranty Start Date on or after 1/9/20 for a maximum of 7 years (unlimited kilometres). Initial 13 months Coverage provided from the Warranty Start Date. The Coverage will be reset for another 13 months from each date that a Participating Isuzu UTE Dealer conducts a Scheduled Service on the vehicle. For full terms & conditions visit isuzuute com au/roadside-assistance-disclaimer

Safety IDAS

Every D-MAX comes with Isuzu's Intelligent Driver Assistance System (IDAS[#]) built-in to protect and enhance the driving experience. IDAS includes smart technologies as well as other passive and active safety features.

*IDAS features are designed to assist the driver, but should not be relied upon nor used as a substitute for safe driving practices. Feature operation may vary in different driving conditions. For full explanation of limitations, see Owner's & Driver's Manual

ANCAP The entire D-MAX range has achieved RATING a maximum 5-star ANCAP safety rating in 2022.

CDECIFICATIONS		1-	2 Hiah E	Sido							А	x4					
SPECIFICATIONS		4x2 High-Ride									4	×4					
	Single Cab	Space	Crew		_	Single Cab	Space				Crew	_		Crew		_	
	Cab Chassis	Čab Chassis	Cab Chassis	Crew Cab Ute	Crew Cab Ute	Cab Chassis	Ċab Chassis	Space Cab Ute	Crew Cab Chassis	Crew Cab Ute	Cab Chassis	Crew Cab Ute	Crew Cab Ute	Cab Chassis	Crew Cab Ute	Crew Cab Ute	Crew Cab Ute
Engine	SX	SX	SX	SX	LS-U	SX	SX	LS-U	SX	SX	LS-M	LS-M	X-RIDER	LS-U	LS-U	LS-U+	X-TERRAIN
1898cc DOHC 4cyl. with intercooled turbocharger (350Nm, 110kW)	•		•	•						•							
2999cc DOHC 4cyl. with intercooled turbocharger (450Nm, 140kW)	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
Transmissions																	
6-speed manual transmission	•					•			•						-		
6-speed "Rev-Tronic" automatic transmission with sequential sport mode	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
Safety and Security		•	•	•	•	•	•	•	•	•	•	•	•	•	•		•
4-channel 4-sensor Anti-lock Brake System (ABS) with Electronic Brakeforce Distribution (EBD) Electronic Stability Control (ESC)																	
Traction Control System (TCS)	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
Emergency Brake Assist (EBA)	•	•	•	•	•	•	•	•	•	•	•	٠	•	•	•	•	•
Hill Start Assist (HSA)	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
Hill Descent Control (HDC) Autonomous Emergency Braking (AEB)																	
Turn Assist with AEB	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
Post-Collision Braking	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
Forward Collision Warning (FCW)	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
Misacceleration Mitigation (*AT models only)	•*	•	•	•	•	•*	•	•	•*	•			•	•		•	•
Intelligent Adaptive Cruise Control (IACC) with Stop and Go functionality Traffic Sign Recognition (TSR)																	
Intelligent Speed Limiter	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
Manual Speed Limiter	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
Lane Departure Warning (LDW)	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
Lane Departure Prevention (LDP)	•	•	•	•	•	•	•	•	•	•			•	•		•	•
Lane Keep Assist (LKA) Emergency Lane Keeping (ELK)																	
Lane Support System (LSS) Switch (disables LDW, LDP, LKA, ELK)	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
Driver Attention Assist	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
Blind Spot Monitoring (BSM)	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
Rear Cross Traffic Alert (RCTA) Rear Cross Traffic Braking (RCTB)						•										•	
BSM/RCTA/RCTB Auto Switch Off (disables BSM/RCTA/RCTB when the genuine tow harness is connected)																	
Digital Reversing camera w/ Dynamic Guidelines				•	•			•		•		•	•		•	•	•
Digital Reversing camera	•	•	•			•	•		•		•			•			
Rear Park Assist Sensors					•			•				•	•		•	•	•
Front Park Assist Sensors 8 Airbags: dual front, curtain, side, driver's knee and far side airbags		•		•			•			•				•			
Passenger side SRS airbag on/off switch	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
Height-adjustable upper mounts for front seat belts	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
Pre-tensioners with load limiters for front seat belts	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
Pre-tensioners with load limiters for outer rear seat belts			•	•	•				•	•			•	•		•	•
3-point retractable seat belts for all rear and centre seating positions Intelligent seatbelt reminder (all seats)		•															
2 childseat tethers and ISO FIX compatible anchor points		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
Height-adjustable head restraints for full-size seats		•	٠	•	•		•	•	•	•	•	•	•	٠	•	•	٠
Integrated head restraint on front seats	•		_	_		•			_	_		_	_	_			_
Child-proof rear door locks Single 10 inch servo brake master cylinder																	
Side anti-intrusion bars inside all doors				•		•			•								
Engine immobilizer	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
Rear window demister		•	•	•	•		•	•	•	•	•	•	•	•	•	•	•
High Density Polyethylene (HDPE) fuel tank	•	•		•	•	•	•	•	•	•	•	•	•	•	•	•	•
High mount brake light on cabin Dual horn																	
Protection	-	•	•	•	•	•	•	•	•	•	•	•	•		•	•	•
Under-front steel skid plate	٠	•	•	٠	٠	•	•	•	•	•	•	•	•	•	•	•	•
Steel plate guards: sump, transfer case, fuel tank leading edge; reinforced resin under fuel tank						•	•	•	•	•	•	•	•	•	•	•	•
Suspension and Brakes				•				-				•			•	-	-
Standard rear leaf suspension Heavy duty rear leaf suspension				•	•			•		•	•	•	•		•	•	•
Front independent, coil spring suspension w/gas shock absorbers, upper and lower wishbones and stabiliser bar	•	•		•	•	•	•	•	•	•	•	•	•	•	•	•	•
Heavy-duty brakes: 320mm ventilated front discs w/twin-pot calipers, 295mm rear drums	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•

SPECIFICATIONS		4x	2 High-F	lide		4x4												
	Single Cab Chassis	Space Cab Chassis	Crew Cab Chassis	Crew Cab Ute	Crew Cab Ute	Single Cab Chassis	Space Cab Chassis	Space Cab Ute		Cab Ute	Crew Cab Chassis		Crew Cab Ute	Crew Cab Chassis	Crew Cab Ute	Crew Cab Ute		
In-cabin Storage	SX	SX	SX	SX	LS-U	SX	SX	LS-U	SX	SX	LS-M	LS-M	X-RIDER	LS-U	LS-U	LS-U+	X-TERRAI	
Lower glovebox compartment only	•	•	•	•		•	•		•	•								
Upper and lower glovebox compartments		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	
Power outlet in lower instrument panel	•	٠	٠	٠	•	•	•	•	•	•		•	•	•	•	•	•	
Centre floor console	•	•	•	٠	•	•	•	•	•	•	•	•	•	•	•	•	•	
Dual-purpose driver and front passenger cup holder tray	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	
Rear passenger door cup holders			•	•	•				•	•	•	•	•	•	•	٠	•	
Pockets on backs of front seats					•			•			•	•	•	•	•	•	•	
Overhead console with twin map lights and flip-down sunglasses case	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	
Front door storage compartment with bottle bulge 2 coat hooks	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	
Flip up convenience hook behind passenger front seat					•			•			•	•	•	•	•	•	•	
Tool storage behind rear seats			٠	٠	•				•	•	٠	٠	•	•	•	٠	•	
Tool storage behind front seats	•	•				•	•	•										
Rear Tub																		
Double-walled ute tub				•	•			•		•		•	•		•	•	•	
4 cargo tie-down hooks inside ute tub				•	•			•		•		•	•		•	٠		
Under rail tub liner					٠			٠							٠	٠	•	
2 cargo tie-down hooks inside ute tub															-	-	•	
Tailgate Assist				•	•			•		•		•	•		•	•	•	
Exterior Style																		
Short front overhang for optimal manoeuvrability and approach angle	•	٠	٠	•	٠	•	•	•	•	•	•	•	•	•	•	•	•	
Halogen multi-reflector projector lens headlights for extra low beam depth & reduced flare & integrated turn indicators	•	•	•	•		•	•		•	•								
Bi-LED headlights with auto-levelling function and integrated turn indicators Automatic headlights		•		•		•	•			•								
Automatic headiights																		
Coming home light																		
Headlight Welcome light	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	
LED Daytime Running Lights (DRLs)					•			•			•	•	•	•	•	•	•	
LED fog lights					•			•			٠	•	•	•	•	٠	•	
Material Black radiator grille	•	•	٠	•		•	•		•	•			•					
Black-Grey radiator grille											•	•						
Silky Silver radiator grille					•			•						•	•	•		
Dark Grey radiator grille																		
Colour-coded front bumper Colour-coded integrated rear step bumper		•				•	•		•		•		•	•				
Black integrated rear step bumper				•	•			•		•		•	•		•	•	•	
Black rear bumper	•	•	•			•	•		•		•		-	•				
Factory fitted tow bar receiver					•			•						•	•	•	•	
Space cab rear "wing" doors		•					•	•										
Aluminium side steps					•			•						•	•	•		
Dark Grey side steps													•				•	
Black door and tailgate handles	•	•	•	•		•	•		•	•	•							
Colour-coded door and tailgate handles Chrome door and tailgate handles											•	•						
Dark Grey door and tailgate handles					•			•						•	•	•	•	
Basalt Black door and tailgate handles													•					
Lockable tailgate				٠	•			•		•		•	•		•	٠	•	
Dark Grey Aero Sports Bar																	•	
Black Sports Bar													•					
Matte Black roller tonneau																	•	
Soft tonneau cover													•					
Dark Grey front and rear underbody spoilers																	•	
Black front underbody spoiler Dark Grey fender flares													•					
Dark Grey roof rails																		
Black power door mirrors	•	•	•	•		•	•		•	•							•	
Colour-coded power door mirrors with integrated turn indicators		-				-	-			-	•	•						
Basalt Black power door mirrors with integrated turn indicators													•					
Chrome fold-in power door mirrors with integrated turn indicators					•			٠						•	٠	٠		
Dark Grey fold-in power door mirrors with integrated turn indicators																	•	
Heated door mirrors Centre front roof-mounted bee-sting aerial					•		-	•		-	-	-		•	•	•	•	
								_			-	-	-				•	

SPECIFICATIONS		4x2	2 High-F	Ride							4	x4					
JECIFICATIONS			-														
	Single Cab	Space Cab	Crew Cab	Crew	Crew	Single Cab	Space Cab	Space			Crew Cab	Crew	Crew	Crew Cab	Crew	Crew	Crew
	Chassis SX	Chassis SX	Chassis SX	Cab Ute SX	Cab Ute LS-U	Chassis SX	Chassis SX	Cab Ute LS-U	Chassis SX	Cab Ute SX	Chassis LS-M	Cab Ute LS-M	Cab Ute X-RIDER	Chassis LS-U	Cab Ute LS-U	Cab Ute	Cab Ute X-TERRAI
Seating	0,1	0/1	0,1	0,1		0/1	0,1	20 0	0/1	0,1				20 0	20 0	20 01	
Standard Black cloth seats	•	•	٠	•		•	٠		٠	•							
High Grade cloth seats					•			•			•	•	•	•	•		
Leather Accented seats																•	
Leather Accented seats with Red Stitching																	•
Front bucket whiplash protection seats	•	•	٠	•	•	•	٠	•	•	•	•	٠	•	•	•	•	•
6-way adjustable driver seat	•	•	٠	•	•	•	٠	•	•	٠	٠	•	•	•	٠		
8-way electric adjustable driver seat																•	•
Electric adjustable lumbar support (driver seat only)					•			•						•	•	•	•
Heated front seats																•	•
Split-fold rear seat			•	•					•	•							
Split-fold rear seat with centre arm rest					•						•	•	•	•	•	•	•
Rear centre seat headrest			٠	•	•				•	•	•	•	•	•	•	•	•
Cabin Amenities																	
Dual zone climate control air-conditioning with integrated heater/demister					•			•						•	•	•	•
Manual air-conditioning with integrated heater/demister	•	•	•	•		•		•	•	•		•			•	•	•
Rear seat air-conditioning vents		-			•	-	-								•	•	•
Pollen and fine particle air filter	•	•			•	•	•	•									
Power windows with one-touch up/down driver's window with safety stop and delay closing																	
Comfort turn signal						•											
Central locking with keyless entry						•											
Smart keyless entry		-	-	-		-	-		-	-	-	-	-				
Walk away lock																	
Remote key auto re-lock	•	•		•		•	•		•			•	•				
Push button start		•	•	•		•	•		•	•	•	•	•				
Remote engine start																	
Power-adjustable door mirrors with turn indicator lights					•							•	•	•	•		
Power-adjustable door mirrors	•	•	•	•	-	•	•	-	•	•	-	-	-	-	-	-	-
4 speaker sound system	•	•	•	•		•	•		•	•							
6 speaker sound system								•			•	•	•				
"Sky Sound" roof-mounted sound system with 8 speakers (mounted in front dash, front doors, rear doors and root)				•									•	•	•	•
9 inch touchscreen display with wireless Apple CarPlay® and wireless Android Auto® with MID Integration	,				•			•						•	•	•	•
8 inch touchscreen display with wireless Apple CarPlay® and wireless Android Auto™	•	•	٠	•		•	٠		•	٠	٠	•	•				
Built-in satellite navigation with MID turn-by-turn directions					•			•						•	•	•	•
Rear centre console USB charging port			•	•	•				•	•	•	•	•	•	•	•	•
USB type C port in central instrument panel					•			•						•	٠	•	•
USB type C port in Touchscreen	•	•	٠	•		•	٠		•	•	٠	•	•				
USB type C port in rear floor console			٠	•	•				•	٠	٠	٠	•	•	•	•	•
USB type A port in Stereo Camera Housing	•	•	•	•	•	٠	•	•	•	٠	•	•	٠	•	•	•	•
Tilt and telescopic adjustable steering wheel with electric power steering	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
Urethane steering wheel with cruise, audio and voice recognition controls	•	•	٠	•		•	٠		•	•	٠	•	•				
Leather steering wheel with cruise, audio and voice recognition controls					•			•						•	•	•	•
4.2 inch Smart MID with digital speedometer, safety information, fuel economy and range, odometer, trip information and service reminder	•	•	•	٠		•	•		•	٠	٠	٠	•				
7 inch Smart MID with digital speedometer, safety information, fuel economy and range, odometer, trip information and service reminder					•			٠						•	•	٠	•
Tyre Pressure Monitoring System (TPMS)					•			•						•	•	•	•
Electro-luminescent gauges	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
"Terrain Command" 4x4 select dial						•	•	•	•	•	•	•	•	•	•	•	•
Rear differential lock button						•	•	•	•	•	•	•	•	•	•	•	•
Rough Terrain Mode button						•	•	•	•	•	•	•	٠	•	•	•	•
Automatic windshield wipers	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
Intuitive flat wiper blade					•			•						•	•	•	•
Day/night interior rear view mirror	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
Auto-dimming rear view mirror					•			•						•	•	•	•
Sun visors with vanity mirrors (driver and passenger) and ticket retaining strap (driver)					•			•						•	•		
Sun visors with illuminated vanity mirrors (driver and passenger) and ticket retaining strap (driver)																•	•
Fixed A-pillar assist-grips for driver and front passenger	•	•	٠	•	•	•	•	•	•	•	٠	•	•	•	•	•	•
Fixed B-pillar assist-grips for rear passengers			•	•	•				•	•	•	•	•	•	•	•	•
Folding assist-grips for driver and front passenger			٠	•	•				٠	•	•	•	•	•	•	•	•
Folding assist-grips for rear passengers			•	•	•				•	•	•	•	•	•	•	•	•
Carpet flooring Easy-clean vinyl flooring					•			•						•	•	•	

Apple CarPlay is a trademark of Apple Inc. Android Auto is a trademark of Google LLC. Not all devices will be compatible & functionality will vary depending on the device. Mobile Data & SMS rates may apply & are the responsibility of the user. Please check your local road rules before using these functions.

FUEL, WEIGHTS			4	x2 Hig	h-Ride				4x4													
& DIMENSIONS	Cab Čab		Space Cab Chassis SX	Čab Cab Chassis Chassis SX SX		Crew Cab Ute SX 1.9L 3.0L		Crew Cab Ute LS-U	Single Cab Chassis SX	Space Cab Chassis SX	Space Cab Ute LS-U	Crew Cab Chassis SX	o Crew Cab Ute SX 1.9L 3.0L		Crew Cab Chassis LS-M	Crew Cab Ute LS-M	Crew Cab Ute X-RIDER	Crew Cab Chassis LS-U	Crew Cab Ute LS-U	Crew Cab Ute LS-U+	Crew Cab Ute X-TERRAI	
Transmission (MT = Manual, AT = Automatic)	MT/AT	MT/AT	AT	AT	3.0L AT	AT	AT	AT	MT / AT	AT	AT	MT / AT	AT	AT	AT	AT	AT	AT	AT	AT	AT	
FUEL CONSUMPTION (litres/100km)	WII/AI	WHI/AI	A	A1	A	Ai	A	A	WIT / AI	A	~	WIT / AI	~	~	Ai	~	A	A1	A1	A	~	
Combined	7.0	8.0	8.0	7.0	8.0	6.7	7.7	8.0	8.0	8.0	8.0	8.0	6.9	8.0	8.0	8.0	8.0	8.0	8.0	8.0	8.0	
Urban	7.9	10.2/9.8	9.8	7.9	9.8	8.3	9.5	9.8	10.2/9.8	9.8	9.8	10.2/9.8	8.1	9.8	9.8	9.8	9.8	9.8	9.8	9.8	9.8	
Extra Urban	6.6	6.7/6.9	6.9	6.6	6.9	6.0	6.7	6.9	6.7/6.9	6.9	6.9	6.7/6.9	6.3	6.9	6.9	6.9	6.9	6.9	6.9	6.9	6.9	
CO ² (g/km)		,							,			,										
Combined	184	206/207	207	184	207	177	200	207	206/207	207	207	206/207	180	207	207	207	207	207	207	207	207	
Urban	208	262/254	254	208	254	218	246	254	262/254	254	254	262/254	212	254	254	254	254	254	254	254	254	
Extra Urban	174	174/180	180	174	180	158	174	180	174/180	180	180	174/180	165	180	180	180	180	180	180	180	180	
Dimensions (mm unless stated otherwise)		,							,			,										
Wheelbase	31	25	3125	0	125	01	125	3125	2105	3125	3125	3125	0.1	25	3125	3125	3125	3125	3125	3125	3125	
Overall length	53		3125 5300	3125 5300			125 280	5285	3125 5340	3125 5300	3125 5285	3125 5300		25 180	3125 5300	5280	3125 5305	3125 5300	3125 5285	5285	53125	
Overall width (excluding door mirrors)	18		1870		370		370	1870	1870	1870	1870	1870		870	1870	1870	1870	1870	1870	1870	1880	
Overall height (*depends on body fitted)	18		1870					1870	1790*	1870	1870	1870		85	1870	1870	1870	1870	1870	1870	1880	
Front overhang		90 90	890		1800*		1785 890		890	890	890	890		90	890	890	890	890	890	890	905	
Rear overhang (*depends on body fitted)	13		1270*	890		1250		890 1250	1310*	890 1270*	1250	1270*		90 !50	1270*	1250	1250	1270*	1255	1255	905 1255	
Wheel track width	15		1270		1270*		1570		1570	1270	1250	1270		50 70	1270	1250	1250	1270	1255	1255	1255	
Ground clearance		35	235	1570			35	1570 240	235	235	240	235		35	235	235	235	240	240	240	240	
Turning circle diameter between kerbs (metres)		2.5	12.5	235 12.5			2.5	12.5	12.5	12.5	12.5	12.5		2.5	12.5	12.5	12.5	12.5	12.5	12.5	12.5	
Approach angle	29		29.6°		2.5 9.6°	29.6°/30°		30.5°	29.6°	29.6°	30.5°	29.6°		0°	29.6°	30°	26.9°	30°	30.5°	30.5°	27.3°	
Departure angle	23		25.3°		5.3°	23.9°		19.0°	24.6°	25.3°	19.0°	25.3°	23		25.3°	23.9°	23.9°	20.6°	19.0°	19.0°	19.0°	
Ramp-over angle	23		23.9°		3.9°		3.3°	23.8°	24.0°	23.9°	23.3°	23.9°	23		23.9°	23.3°	23.3°	20.0 24.3°	23.8°	23.8°	23.8°	
	20	.0	20.0	20		20		20.0	20.0	20.0	20.0	20.0	20		20.0	20.0	20.0	24.0	20.0	20.0	20.0	
Load area (mm)	10	10	705		50			150	10.10	705	705	150			150	150	450	150	450	150	150	
Cab to rear axle	12	40	765	4	50		50	450	1240	765	765	450		50	450	450	450	450	450	450	450	
Length (top)	0.51	-	-	10	-		195	1495	-	-	1805	-		95	-	1495	1495	-	1495	1495	1495	
Length (floor) (*inside genuine accessory tray body)	25		2100*		00*		570	1570	2550*	2100*	1835	1800*		70	1800*	1570	1570	1800*	1570	1570	1570	
Maximum width (*inside genuine accessory alloy tray body)	173	//*	1777*	17	77*		530	1530	1777*	1777*	1530	1777*		30	1777*	1530	1530	1777*	1530	1530	1530	
Width between wheel houses		-	-		-		22	1122	-	-	1122	-		22	-	1122	1122	-	1122	1122	1122	
Depth		-	-		-	4	90	490	-	-	490	-	4	90	-	490	490	-	490	490	490	
Interior (mm)																						
Leg room - front	10	75	1075)75)75	1075	1075	1075	1075	1075		175	1075	1075	1075	1075	1075	1075	1075	
Leg room - rear		-	-		05		05	905	-	-	-	905		05	905	905	905	905	905	905	905	
Shoulder room - front		60	1460		160		160	1460	1460	1460	1460	1460		60	1460	1460	1460	1460	1460	1460	1460	
Head room - front	10	20	1020	10	020	10)20	1020	1020	1020	1020	1020	10	20	1020	1020	1020	1020	1020	1020	1020	
Rear cargo space		-	730		-		-	-	-	730	730	-		-	-	-	-	-	-	-	-	
Mass (kg)																						
Gross Vehicle Mass (GVM)	3000	3000	3000	3000	3000	3000	3000	3000	3100	3100	3100	3100	3100	3100	3100	3100	3100	3100	3100	3100	3100	
Kerb weight^	1600/1620	1695/1705	1780	1745	1830	1870	1950	2015	1785/1790	1865	2065	1910/1915	1955	2035	1910	2030	2055	1965	2105	2110	2170	
Payload ⁻ (cab chassis models: final mass depends on body fitted)	1400/1380	1305/1295	1220	1255	1170	1130	1050	985	1315/1310	1235	1035	1190/1185	1145	1065	1190	1070	1045	1135	995	990	930	
Gross Combination Mass (GCM)	5300/5500	5850	5850	5500	5850	5500	5850	5850	6000	6000	6000	6000	5500	6000	6000	6000	6000	6000	6000	6000	6000	
Maximum towing mass (braked trailer)	2800/3000	3500	3500	3000	3500	3000	3500	3500	3500	3500	3500	3500	3000	3500	3500	3500	3500	3500	3500	3500	3500	
Maximum towing mass (non-braked trailer)	750	750	750	750	750	750	750	750	750	750	750	750	750	750	750	750	750	750	750	750	750	
Maximum tow ball download (when fitted with genuine Isuzu UTE tow kit)	280/300	350	350	300	350	300	350	350	350	350	350	350	300	350	350	350	350	350	350	350	350	
Fuel tank capacity (litres)	76	76	76	76	76	76	76	76	76	76	76	76	76	76	76	76	76	76	76	76	76	

⁴Fuel consumption & emissions figures based on ADR 81/02 & are to be used for vehicle comparison purposes only. Actual fuel consumption & emissions will vary depending on many factors including, but not limited to, traffic conditions, individual driving style & vehicle condition. [^]Kerb weight - unladen mass of vehicle & full tank of fuel, excludes tray body for cab chassis vehicles. Fuel weight ratio is based on Fuel Standard (Automotive Diesel) Determination 2001. ⁻Payload equals GVM minus kerb weight.

CAB CHASSIS BODY STYLES AND DIMENSIONS (24MY)





SX Space Cab Chassis 4x2 & 4x4




SX Crew Cab Chassis 4x2 & 4x4











SX Single Cab Chassis 4x2 & 4x4



















LS-M Crew Cab Chassis 4x4























CAB CHASSIS AND UTE BODY STYLES AND DIMENSIONS (24MY)






SX Crew Cab Ute 4x2 & 4x4



LS-M Crew Cab Ute 4x4





X-RIDER Crew Cab Ute 4x4





LS-U Crew Cab Chassis 4x4














































UTE BODY STYLES AND DIMENSIONS (24MY)



LS-U Space Cab Ute 4x4












LS-U Crew Cab Ute 4x2 & 4x4 LS-U+ Crew Cab Ute 4x4












X-TERRAIN Crew Cab Ute 4x4







COLOURS AND TRIM (24MY)

Body Colours













Obsidian Grey mica



Mercury Silver metallic









Magnetic Red mica (X-RIDER, LS-U Range & X-TERRAIN Exclusive)



Granite Grey mica (X-RIDER, LS-U Range & X-TERRAIN Exclusive)



Moonstone White pearl (LS-U Range & X-TERRAIN Exclusive)



Sunstone Orange mica (X-TERRAIN Exclusive)

Interior Trim



Standard Black Cloth (On SX models)

High Grade Cloth (On LS-M, X-RIDER, LS-U models)

Leather Accented (On LS-U+)



Leather Accented¹ with Red Stitching (On X-TERRAIN)

*Seats have leather touches or accents, but are not wholly leather. Colours depicted herein may differ from actual due to the printing process.

TRAY STYLES

Economy Alloy

General Purpose Alloy

Heavy Duty Alloy

Heavy Duty Steel

Mine Specification Steel















Space

Crew















Please read with the 24MY Isuzu D-MAX vehicle brochure. All information is true and correct at the time of publishing, April 2024. Isuzu UTE Australia reserves the right to change specifications and features at any time. Colours depicted herein may differ from actual. Please refer to isuzuute.com.au or consult your authorised Isuzu UTE Dealer for current availability of models, options, specifications, colours and Isuzu UTE Genuine Accessories.

