24MY ISUZU MU-X SPECIFICATIONS

Engine	3.0L	1.9L
Series	Isuzu 4JJ3-TCX	RZ4E-TC
Description	3.0 litre turbo-diesel, in-line 4-cylinder, DOHC, 16-valve with Diesel Particulate Diffuser (DPD)	1.9-litre turbo-diesel, in-line 4-cylinder, DOHC, 16-valve with Diesel Particulate Diffuser (DPD)
Maximum torque	450Nm @ 1600→2600 rpm (automatic)	350Nm @ 1800→2600 rpm (automatic)
Maximum power	140kW @ 3600 rpm	110kW @ 3600 rpm
Bore x stroke	95.4mm x 104.9mm	80mm x 94.4mm
Displacement	2999сс	1898cc
Compression ratio	16.3 : 1	15.9: 1
Cylinder head	Isuzu-patent special aluminium alloy	Isuzu-patent special aluminium alloy
Valve gear	Chain-driven dual overhead camshafts, roller rockers, 4 valves/cylinder	Chain-driven dual overhead camshafts, roller rockers, 4 valves/cylinder
Induction	Electronic high pressure common rail direct fuel injection with VSS (Variable Swirl System) and intercooled electric control VGS (Variable Geometry System) turbocharger	Electronic high pressure common rail direct fuel injection with VSS (Variable Swirl System) and intercooled electric control VGS (Variable Geometry System) turbocharger
Cylinder block	Cast iron upper with induction-hardened cylinder bores, cast alloy lower	Cast iron upper with induction-hardened cylinder bores, cast alloy lower
Emission level	Euro 5	Euro 5
Alternator	120 amp with Intelligent Battery Sensor (IBS)	120 amp with Intelligent Battery Sensor (IBS)

Transmissions

Transmission	S					
Automatic	Aisin AWR6B45 II 6-speed with sequential shift and brake shift lock electronically controlled, tri-mode with Adaptive Logic Control and fuel-saving lock-up torque converter on gears 3, 4, 5 and 6 • Uphill/Downhill Transmission Control: holds gear in varied-gradient ascents, selects gear on steep descents to hold speed with engine braking					
Ratios: 1	6-speed Automatic 1st 2nd 3rd 4th 5th 6th Reverse	3.600 2.090 1.488 1.000 0.687 0.580 3.732				
Final drive	4x2 / 4x4 3.0L 4JJ3-TCX 4x2 / 4x4 1.9L RZ4E-TC	3.727 4.100				
	Snorkelled diff breathers to increase fording depth and reduce mud blockage					
Transfer gearing	4x4 low-range 4x4 high-range	2.482 1.000				
4x4 system		ain Command" control with 'shift on the fly' to 100km/h, 4-low with rear differential lock				
Drivetrain system	TCS (Traction Control System) on all model variants					

Steering

Electric power steering with speed-sensing steering feel (light at low speed, heavy at high speed); tilt and telescopic adjustable steering wheel

Speed-sensitive variable capacity Electric power system; 3.84 turns lock-to-lock via tilt-adjustable steering wheel

Chassis

Frame

Ladder frame chassis constructed with high-tensile steel with 9 crossmembers

Front suspension

Independent, high-ride, coil springs, gas shock absorbers, upper and lower wishbones, stabiliser bar

Rear suspension

Multi-link coil suspension, gas shock absorbers, stabiliser bar

Axles

Front

Independent 4x4: fully floating with outer CV, inner double offset joints and equal length driveshafts. Rating: 1450kg

Rear

Rigid semi-floating banjo with hypoid final drive and dual tapered needle roller bearings. Rating: 1650kg

Brakes

Anti-lock Brake System (ABS) with Electronic Brakeforce Distribution (EBD), Electronic Stability Control (ESC), Emergency Brake Assist (EBA), Traction Control System (TCS), Roll Over Mitigation, Hill Start Assist (HSA), Hill Descent Control (HDC) and Trailer Sway Control (TSC)

All models: 320mm dia. ventilated front discs with 2-piston calipers, 318mm dia. ventilated rear discs with 1-piston calipers

Power-assisted via 10" servo unit; central electrical switch park brake

Wheels and Tyres

4x4 & 4x2 LS-M	17" x 7" alloy; 255 / 65 R17 All-Terrain
4x4 & 4x2 LS-U	18" x 7.5" alloy; 265 / 60 R18 Highway-Terrain
4x4 & 4x2 LS-T	20" x 7.5" alloy; 265 / 50 R20 Highway-Terrain
Spare	LS-M & LS-U Models: full size steel spare wheel LS-T Models: full size alloy spare wheel

Service Plus

Warranty	For the ultimate peace of mind, every Isuzu MU-X comes standard with a comprehensive, bumper-to-bumper 6 years/150,000km warranty^.
Roadside Assistance	Enjoy up to 7 years Roadside Assistance< when you complete your scheduled services at a Participating Isuzu UTE Dealer.
Flat Price Servicing	As an owner you will get access to our Flat Price Servicing ⁵ Program. The FPS Program covers the first 5 Scheduled Services at \$449 per service in line with the Scheduled Service Intervals.

*The Flat Price Servicing Program ("FPS Program") applies to FPS Eligible Vehicles (excludes Rental & Government Customers) at Participating Isuzu UTE Dealers only. For 24MY and later vehicle models, the Flat Price Servicing covers the first 5 Scheduled Services up to 5 years/75,000km (whichever occurs first). FPS Program is subject to change. For full terms & conditions, current pricing & model eligibility visit isuzuute.com.au/flat-price-service-disclaimer. "6 years/150,000km (whichever occurs first), for Isuzu UTE Vehicles with a Warranty Start Date on or after 1/1/19. Excludes trays & accessories. *The Roadside Assistance Program ("RSA Program") provides Coverage to RSA Eligible Vehicles (Private, ABN and Business Fleet Customers only with a Warranty Start Date on or after 1/9/20 for a maximum of 7 years (unlimited kilometres). Initial 13 months Coverage provided from the Warranty Start Date on or after another 13 months from each date that a Participating Isuzu UTE Dealer conducts a Scheduled Service on the vehicle.



Safety

IDAS

Every MU-X comes with Isuzu's Intelligent Driver Assistance System (IDAS*) built-in to protect and enhance the driving experience. IDAS includes smart technologies as well as other passive and active safety features.

*IDAS features are designed to assist the driver, but should not be relied upon nor used as a substitute for safe driving practices. Feature operation may vary in different driving conditions. For full explanation of limitations, see Owner's & Driver's Manual.



ANCAP RATING

The entire MU-X range has achieved a maximum 5-star ANCAP safety rating in 2022.



SPECIFICATIONS		4x2			4x4	
SPECIFICATIONS						
Engine	LS-M	LS-U	LS-T	LS-M	LS-U	LS-T
_ =					_	
1898cc DOHC 4cyl, with intercooled turbocharger (350Nm, 110kW)	•	_	_	•	•	_
2999cc DOHC 4cyl. with intercooled turbocharger (450Nm, 140kW)	•	•	•	•	•	•
Transmissions						
6-speed "Rev-Tronic" automatic transmission with sequential sport mode	•	•	•	•	•	•
Safety and Security						
4-channel 4-sensor Anti-lock Brake System (ABS) with Electronic Brakeforce Distribution (EBD)	•	•	•	•	•	•
Electronic Stability Control (ESC)	•		•		•	
Traction Control System (TCS)	•	•	•	•	•	•
Emergency Brake Assist (EBA)	•	•	•	•	•	•
Hill Start Assist (HSA)	•	•	•	•	•	•
Hill Descent Control (HDC)	•	•	•	•	•	•
Roll-Over Mitigation (ROM)	•	•	•	•	•	•
Autonomous Emergency Braking (AEB)	•	•	•	•	•	•
Turn Assist with AEB	•	•	•	•	•	•
Post-Collision Braking (PCB)	•	•	•	•	•	•
Forward Collision Warning (FCW)	•	•	•	•	•	•
Misacceleration Mitigation	•	•	•	•	•	•
Adaptive Cruise Control (ACC) with Stop and Go Functionality	•	•	•	•	•	•
Traffic Sign Recognition (TSR)	•	•	•	•	•	•
Intelligent Speed Limiter	•	•	•	•	•	•
Manual Speed Limiter	•	•	•	•	•	•
Lane Departure Warning (LDW)	•	•	•	•	•	•
Lane Departure Prevention (LDP)	•	•	•	•	•	•
Lane Keep Assist (LKA)	•	•	•	•	•	•
Emergency Lane Keeping (ELK)	•	•	•	•	•	•
Lane Support System (LSS) Switch (disables LDW, LDP, LKA, ELK)	•	•	•	•	•	•
Driver Attention Assist	•	•	•	•	•	•
Blind Spot Monitoring (BSM)	•	•	•	•	•	•
Rear Cross Traffic Alert (RCTA)	•	•	•	•	•	•
BSM/RCTA Auto Switch Off (disables BSM/RCTA when the genuine tow harness is connected)	•	•	•	•	•	•
Reversing Camera with dynamic guidelines	•	•	•	•	•	•
Front Park Assist Sensors		•	•		•	•
Rear Park Assist Sensors	•	•	•	•	•	•
8 Airbags: dual front, curtain, side, driver's knee and far side airbags	•	•	•	•	•	•
Passenger side SRS airbag on/off switch	•	•	•	•	•	•
Height-adjustable upper mounts for front seat belts	•	•	•	•	•	•
Pre-tensioners with load limiters for front seat belts	•	•	•	•	•	•
Pre-tensioners with load limiters for outer second row seat belts	•	•	•	•	•	•
3-point retractable seat belts for third row and centre seating positions	•	•	•	•	•	•
Intelligent seatbelt reminder (all seats)	•	•	•	•	•	•
Three childseat top tethers for second row	•	•	•	•	•	•
Two ISO FIX compatible anchor points for second row	•	•	•	•	•	•
Height-adjustable head restraints for all seats	•	•	•	•	•	•
Child-proof rear door locks	•	•	•	•	•	•
Anti-theft alarm	•	•	•	•	•	•
Side anti-intrusion bars inside all doors	•	•	•	•	•	•
Engine immobilizer	•	•	•	•	•	•
Rear window demister with timer and intermittent wiper	•	•	•	•	•	•
High Density Polyethylene (HDPE) fuel tank	•	•	•	•	•	•
High mount brake light on tailgate	•	•	•	•	•	•
Dual horn	•	•	•	•	•	•
Protection						
Under-front steel skid plate	•	•	•	•	•	•
Steel plate guards: sump, transfer case, fuel tank leading edge; reinforced resin under fuel tank				•	•	•
Suspension and Brakes						
Electric Park Brake with Auto Hold feature		•			•	
Single 10 inch servo brake master cylinder						
Rear 5-link coil suspension with stabiliser bar		•			•	
		•				
Front independent, coil spring suspension w/gas shock absorbers, upper and lower wishbones and stabiliser bar						

SPECIFICATIONS

					TAT	
SPECIFICATIONS						
eating	LS-M	LS-U	LS-T	LS-M	LS-U	LS-1
ligh grade cloth seats	•	•		•	•	
ingligible sold in soul	•	•		•		•
ront bucket whiplash protection seats	•	•		•		•
-way adjustable driver seat			•			•
-way adjustable driver seat	•					
electric adjustable lumbar support (driver seat only)						
-way electric adjustable front passenger seat		•			•	
0:40 reclining split-fold second row seats with fold away centre arm rest		•				
io.40 reclining split-fold third row seats with fold away centre arm rest						
	•	•		•	•	
/ariable heated front driver and passenger seats						•
n-cabin Storage						
Jpper and lower glovebox compartments	•	•	•	•	•	•
Power outlet in lower instrument panel	•	•	•	•	•	•
Centre floor console with two USB ports	•	•	•	•	•	•
Dual-purpose driver and front passenger cup holder tray	•	•	•	•	•	•
Rear passenger door cup holders	•	•	•	•	•	•
econd row fold out cup holder/storage tray	•	•	•	•	•	•
hird row outer armrests with integrated cup holders	•	•	•	•	•	•
Pockets on backs of front seats	•	•	•	•	•	•
Overhead console with twin map lights and flip-down sunglasses case	•	•	•	•	•	•
ront door storage compartment with bottle bulge	•	•	•	•	•	•
wo coat hooks	•	•	•	•	•	•
lip up convenience hook behind passenger front seat	•	•	•	•	•	•
Storage space under rear cargo flooring	•	•	•	•	•	•
Tool storage space inside rear cargo wall (driver side)	•	•	•	•	•	•
exterior Style						
-				•		
Short front overhang for optimal manoeuvrability and approach angle		•	•	•	•	
Bi-LED headlights with auto-levelling function		•				
Automatic headlights		•	•	•	•	•
Automatic high beam		•	•	•	•	•
Coming home light	•	•	•	•	•	•
ED Daytime Running Lights (DRLs)	•	•	•	•		•
ED fog lights		•	•		•	•
Black and gunmetal grey grille	•			•		
Aagnetite and black chrome grille		•	•		•	•
Colour-coded front bumper	•	•	•	•	•	•
Black aluminium side steps	•			•		
Aagnetite aluminium side steps		•	•		•	•
lack door handles	•			•		
Colour-coded door handles		•	•		•	•
Nanual tailgate with integrated rear spoiler	•			•		
lands-free power tailgate with integrated rear spoiler		•	•		•	•
colour-coded power fold-in door mirrors with integrated turn indicators		•	•		•	•
Black power door mirrors	•			•		
lear privacy glass		•	•		•	•
eated door mirrors		•	•		•	•
entre front roof-mounted bee-sting aerial	•	•	•	•	•	•
Roof rails (maximum load capacity 100kg)		•	•		•	•
ED rear combination lamps	•					

4x2

4x4

SPECIFICATIONS

	LS-M	LS-U	LS-T	LS-M	LS-U	LS-T
Cabin Amenities						
Dual zone climate control air-conditioning with integrated heater/demister		•	•		•	•
Manual air-conditioning with integrated heater/demister	•			•		
Second and third row air-conditioning vents with controls	•	•	•	•	•	•
Pollen and fine particle air filter	•	•	•	•	•	•
Power windows with one-touch up/down driver's window with safety stop	•	•	•	•	•	•
Comfort turn signal	•	•	•	•	•	•
Central locking with keyless entry	•	•	•	•	•	•
Smart keyless entry		•	•		•	•
Walk away door lock		•	•		•	•
Welcome home light		•	•		•	•
Push button start	•	•	•	•	•	•
Remote engine start			•			•
Ambient door lighting			•			•
Centre console overhead guidelight			•			•
Poweradjustable door mirrors with turn indicator lights		•	•		•	•
Power-adjustable door mirrors	•			•		
4 speaker sound system	•			•		
8 speaker sound system		•	•		•	•
9 inch touchscreen display with Apple CarPlay® and Android Auto™		•	•		•	•
7 inch touchscreen display with Apple CarPlay® and Android Auto™	•			•		
Built-in satellite navigation with MID turn-by-turn directions		•	•		•	•
Two rear centre console USB charging ports	•	•	•	•	•	•
Tilt and telescopic adjustable steering wheel with electric power steering	•	•	•	•	•	•
Urethane steering wheel with cruise, audio and voice recognition controls	•			•		
Leather steering wheel with cruise, audio and voice recognition controls		•	•		•	•
Smart MID with digital speedometer, safety information, fuel economy & range, odometer, trip information and service reminder	•	•	•	•	•	•
Tyre Pressure Monitoring System		•	•		•	•
Electro-luminescent gauges	•	•	•	•	•	•
"Terrain Command" 4x4 select dial				•	•	•
Rear Differential Lock button				•	•	•
Rough Terrain Mode button				•	•	•
Automatic Windshield Wipers	•	•	•	•	•	•
Intuitive Flat Wiper Blade		•	•		•	•
Manual day/night interior rear view mirror	•			•		
Auto-dimming rear view mirror		•	•	_	•	•
Sun visors with vanity mirrors (driver and passenger) and ticket retaining strap (driver)		•	•		•	
Sun visors with vanity mirror (passenger) and ticket retaining strap (driver)	•		-	•		
Fixed A-pillar assist-grips for driver and front passenger		•	•	•	•	•
Fixed B-pillar assist-grips for rear passengers		•		•	•	•
Folding assist-grips for driver and front passenger		•		•	•	
Folding assist-grips for rear passengers		•				
Carpet flooring		•				
12 volt power outlets in lower instrument panel and rear cargo area		-	-		•	

FUEL, WEIGHTS AND DIMENSIONS		4x2			4x4			
MU-X ADR 81/02 ^A Fuel Consumption Values	LS-M 1.9L 3.0L	LS-U	LS-T	LS-M 1.9L 3.0L	LS-U 1.9L 3.0L	LS-T		
Transmission (AT = Automatic)	AT AT	AT	AT	AT AT	AT AT	AT		
FUEL CONSUMPTION (litres/100km)								
Combined	7.4 7.8	7.8	7.8	7.4 8.3	7.4 8.3	8.3		
Urban	9.0 9.6	9.6	9.6	9.0 10.3	9.0 10.3	10.3		
Extra Urban	6.7 6.8	6.8	6.8	6.7 7.2	6.7 7.2	7.2		
CO ² (q/km)								
Combined	196 206	206	206	196 220	196 220	220		
Urban	237 253	253	253	237 271	237 271	271		
Extra Urban	177 179	179	179	177 190	177 190	190		
Dimensions (mm unless stated otherwise)						,		
Wheelbase	2855	2855	2855	2855	2855	2855		
Overall length	4850	4850	4850	4850	4850	4850		
Overall width (excluding door mirrors)	1870	1870	1870	1870	1870	1870		
Overall height	1815	1825	1825	1815	1825	1825		
Front overhang	895	895	895	895	895	895		
Rear overhang	1100	1100	1100	1100	1100	1100		
Wheel track width	1570	1570	1570	1570	1570	1570		
Wilder data with Ground clearance	230	235	235	230	235	235		
Turning circle diameter between kerbs (metres)	11.4	11.4	11.4	11.4	11.4	11.4		
Approach angle	23.4° 28.6°	29.2°	29.2°	23.4° 28.6°	24.0° 29.2°	29.2°		
Departure angle	27.6° 27.6°	26.9°	26.4°	27.6° 27.6°	26.9° 26.9°	26.4°		
Departure angle Ramp-over angle	19.1° 22.6°	20.3 23.1°	23.1°	19.1° 22.6°	19.6° 23.1°	23.1°		
Wading depth [‡]	800	800	800	800	800	800		
Interior	800	000	800	800	800	800		
Leg room - front (mm)	1075	1075	1075	1075	1075	1075		
Leg room - 2nd row (mm)	915	915	915	915	915	915		
Leg room - 3rd row (mm)	850	850	850	850	850	850		
Leg room - foot (mm) Shoulder room - front (mm)	1460	1460	1460	1460	1460	1460		
Head room - front (mm)	1020	1020	1020	1020	1020	1020		
Rear cargo space - 2nd & 3rd row flat (litres)	2138	2138	2138	2138	2138	2138		
Rear cargo space - 3rd row flat (litres)	1119	1119	1119	1119	1119	1119		
Rear cargo space - 3rd row up (litres)	311	311	311	311	311	311		
	311	311	311	311	311	311		
Mass (kg)								
Gross Vehicle Mass (GVM)	2700 2700	2700	2700	2800 2800	2800 2800	2800		
Kerb weight [^]	1975 2050	2065	2090	2065 2140	2080 2160	2180		
Payload~	725 650	635	610	735 665	720 645	620		
Gross Combination Mass (GCM)	5500 5900	5900	5900	5500 5900	5500 5900	5900		
Maximum towing mass (braked trailer)	3000 3500	3500	3500	3000 3500	3000 3500	3500		
Maximum towing mass (non-braked trailer)	750 750	750	750	750 750	750 750	750		
Maximum tow ball download (when fitted with genuine Isuzu UTE tow kit)	300 350	350	350	300 350	300 350	350		
Fuel tank capacity (litres)	80 80	80	80	80 80	80 80	80		

^AFuel consumption & emissions figures based on ADR 81/02 and are to be used for vehicle comparison purposes only. Actual fuel consumption & emissions will vary depending on many factors including, but not limited to, traffic conditions, individual driving style & vehicle condition.


*Up to 800mm of wading depth on all MU-X models when travelling at a consistent speed of 7km/h. Water ingress may occur if speed is not maintained or if the vehicle is static in water above 350mm.


*Kerb weight - unladen mass of vehicle & full tank of fuel. Fuel weight ratio is based on Fuel Standard (Automotive Diesel) Determination 2001. *Payload equals GVM minus kerb weight.

BODY STYLES AND DIMENSIONS (24MY)














Isuzu MU-X LS-U 4x2 and 4x4











Isuzu MU-X LS-T 4x2 and 4x4

